CTL 26 EI AC

Mobile Dust Extractor | CLEANTEC | Festool article 577879

A mains-powered, L-class professional dust extractor with AUTOCLEAN automatic main-filter cleaning, Bluetooth connectivity and a 26-litre container. Designed for suitable dust extraction in workshops and on construction sites.

TECHNICAL SPECIFICATIONS

Dust classification	L
Power consumption	350–1,200 W
Maximum volume flow	3,900 l/min (turbine)
Maximum vacuum	24,000 Pa
Filter surface area	6,318 cm²
Container / filter bag	26 / 24 litres
Dimensions (L × W × H)	630 × 365 × 540 mm
Power cable length	7.5 m
Product weight (without accessories)	14.40 kg
Transport weight (including accessories)	18.20 kg
Drive type	Mains-powered
Maximum tool socket load	2,400 W (variant/market dependent)

CONTROL AND EXTRACTION FEATURES

AUTOCLEAN: Automatic main-filter cleaning; cleaning intervals can be adjusted via the Festool app. **Bluetooth:** Automatic activation with compatible Festool Bluetooth battery packs or an optional remote control. **Tool socket:** Automatic start/stop with compatible mains-powered tools. **Wet/dry:** Wet extraction is supported when prepared according to the operating instructions.

Applications & Equipment

MAIN APPLICATIONS

Dust extraction during compatible woodworking, sanding, sawing and construction work; collection of suitable mineral dust; workshop and site cleaning. Dust class L applies to dust with occupational exposure limits greater than 1 mg/m³. Check material hazards and local requirements before use.

STANDARD SCOPE OF DELIVERY

Main filter	HF-CT 26/36/48 HP
Filter bag	SELFCLEAN filter bag
Disposal bag	Included
Suction hose	D 27/32 × 3.5 m-AS/CTR antistatic suction hose

NOISE AND HANDLING

A-weighted sound pressure level	71 dB(A) (UK 230 V variant data)
Noise uncertainty K	3 dB
Connectivity	Integrated Bluetooth; Festool app
Mobility	Wheeled chassis; hose storage; T-LOC compatibility

SAFETY AND CONFIGURATION NOTES

Use the extractor only for dust types permitted by its L-class classification. Do not use for hazardous dust requiring M- or H-class extraction. For wet extraction, prepare the machine and filters as instructed by Festool. Disconnect mains power before servicing, changing filters or emptying the container. Respect the appliance-socket load rating of the supplied regional variant.

SOURCE AND DOCUMENT STATUS

Prepared from the official Festool CTL 26 EI AC article 577879 listing and Festool UK 230 V variant 577878 technical information. Electrical socket ratings and weight can vary by market. Confirm the supplied variant and its rating plate before publishing region-specific electrical specifications.

This is an independently prepared technical summary, not an official Festool-issued data sheet. Verify current specifications and safety requirements against Festool documentation.