CTM MIDI I

MOBILE DUST EXTRACTOR | CLEANTEC | DUST CLASS M

Compact professional dust extractor for suitable wood and mineral dust. Manual filter cleaning, Bluetooth automatic starting and an M-class airflow warning support mobile installation and workshop tasks.

TECHNICAL SPECIFICATIONS

Dust classification	M (suitable dust with occupational exposure limits above 0.1 mg/m³)
Power consumption	350–1,200 W
Maximum volume flow	3,700 l/min
Maximum vacuum	24,000 Pa
Container / filter bag	15 / 12.5 litres
Filter surface area	3,369 cm²
Dimensions (L × W × H)	470 × 320 × 495 mm
Weight	11.3 kg (published catalogue specification)
Mains cable length	7.5 m
Maximum tool socket load	2,200 W (catalogue configuration; regional limits may differ)
Filter cleaning	Manual; no AUTOCLEAN automatic cleaning
Power-tool starting	Automatic socket operation; Bluetooth compatible battery/remote starting

EXTRACTION AND SAFETY

M-class filtration is intended for appropriate medium-hazard dusts. The extractor monitors airflow and warns of insufficient flow. Match the extractor, filter, hose and disposal method to the material and applicable safety requirements. Do not use for dust requiring H-class containment.

Technical values are maximum or nominal manufacturer-published values; real performance varies with filter condition, hose, accessory and application.

APPLICATIONS & CONFIGURATION

FESTOOL CTM MIDI I | MOBILE DUST EXTRACTOR

FEATURES AND OPERATION

- M-class dust extraction with airflow monitoring and audible warning.
- Manual main-filter cleaning and external, tool-free filter access.
- Integrated Bluetooth automatic starting with compatible Festool battery packs or optional remote.
- Power-tool socket for automatic operation with compatible mains-powered tools.
- Smooth antistatic hose, internal hose storage, cable holder and SYS-Dock / T-LOC compatibility.
- Wet extraction possible with the appropriate wet filter and configuration.

TYPICAL APPLICATIONS

Professional installation, joinery, workshop clean-up, dust extraction from compatible sanders, saws and drills, and service work involving suitable M-class dust. Confirm the applicable dust class for each material.

PUBLISHED PACKAGE CONTENTS — ARTICLE 574822

Main filter	High-performance main filter
Filter bag	SELFCLEAN filter bag
Suction hose	Smooth antistatic D 27/32 × 3.5 m AS/CT hose
Connection	Extraction sleeve with bypass
Organisation	Hose holder, cable holder and SYS-Dock with T-LOC function

PRODUCT IDENTIFICATION AND SOURCES

Model: Festool CLEANTEC CTM MIDI I (non-AUTOCLEAN). Article 574822 is the published international catalogue reference; South African stock numbers and supplied accessories should be confirmed with the local distributor.

Sources: Festool Main Catalogue 2021 and 2022 (festool.com); Festool 2020 product price list; Festool Australia CTM MIDI I product listing (regional article 576740). Specifications are based on the published non-AC version, not the CTM MIDI I AC.

This independently prepared sheet is not an official Festool-issued data sheet. Manufacturer documentation and local safety regulations take precedence.