MX 1200 RE EF HS2

Professional Stirrer | Technical Data Sheet | Article 575813

A mains-powered, single-gear construction mixer with ErgoFix height adjustment, electronic speed control and an HS 2 spiral stirring paddle. Designed for professional preparation of compatible construction materials.

Technical specifications

Power consumption	1,200 W
Gearbox	1 gear
No-load speed	360–630 rpm
Maximum mixing quantity	60 litres
Maximum stirring basket diameter	140 mm
Tool holder	M14 / ErgoFix
Clamping neck diameter	57 mm
Power cable length	4.0 m
Product weight without accessories	6.0 kg
Drive type	Mains-powered

Features and operation

• ErgoFix height adjustment and quick-change adapter for comfortable working height and convenient paddle removal.

• Electronic soft start and variable speed control help reduce splashing and adapt the stirring action to the material.

• Motor electronics support consistent mixing performance; protective labyrinth seal and rubber corners improve durability.

• MX-A dust extraction attachment helps capture airborne powder when filling the mixing bucket; connect to a suitable extractor.

Applications and safety

MX 1200 RE EF HS2 | Article 575813

Typical applications

- Mixing suitable ready-made plaster, gypsum-based materials and levelling compounds.
- Preparing compatible tile adhesives, mortar, cement and concrete mixtures.
- Professional building, renovation and finishing work requiring batches up to 60 litres.

Scope of delivery

Stirring paddle	HS 2 140 × 600 mm M14 spiral stirrer
Adapter	AD-EF-M14/80 ErgoFix adapter
Hand tools	Double open-ended wrench
Dust control	MX-A dust extraction attachment
Packaging	Carton

Noise and vibration (manufacturer figures)

Sound pressure level LpA	85 dB(A)
Sound power level LWA	96 dB(A)
Noise uncertainty K	1.5 dB
Vibration ah	2.5 m/s²
Vibration uncertainty K	1.5 m/s²

Safe operation

- Follow the Festool operating manual and the material manufacturer’s mixing instructions.
- Wear appropriate eye, hearing and respiratory protection; control dust at source.
- Use a stable mixing container; keep hands and loose clothing clear of the rotating paddle.
- Disconnect the power supply before changing accessories, cleaning or servicing.

Source: Festool official product information for article 575813 (festool.de); South African distributor catalogue (vermontsales.co.za).
Note: Independently prepared technical summary. Not an official Festool-issued data sheet. Confirm regional supply configuration and refer to the manufacturer’s current manual before use.